

System	Schüco Alu Inside Nordic
Special features	- / -
Product families	1. Side-hung, top-hung and Top Swing window, outward-opening
Frame material	PVC-U

PVC-U systems  
Windows and doors

Schüco product performance certificate  
In accordance with DIN EN 14351-1:2016-12

Features	Class/value
Resistance to wind load	C3
Resistance to snow and permanent loads	Not relevant**
Reaction to fire	Not relevant**
Watertightness	E1200
Dangerous substances	In accordance with EN14351-1 section 4.6
Impact resistance	npd
Load-bearing capacity of safety devices	npd
Height and width	Not relevant**
Ability to release	Not relevant**
Sound reduction	npd
Thermal transmittance	*
Radiation properties	CE marking for glazing
Air permeability	Class 4
Operating forces	Class 1
Mechanical strength	Class 4
Ventilation	*
Bullet resistance	npd
Blast resistance	npd
Mechanical durability test	npd
Behaviour between different climates	3A / 3D
Burglar resistance	npd

No. KS1007775\_EN-00  
Valid until 01/02/2021

Basic principles  
EN 14351-1 (2006-03)  
Windows and external doors  
The Schüco performance certificate shows the performance characteristics of the systems named with their product families as per the specifications of the product standard.  
The national building regulations and contractual arrangements apply to the use of the performance characteristics.

Publication instructions  
The Schüco International KG license conditions and conditions of use shall apply.

- \* Project-specific certification – if necessary
- \*\* Not mandatory for windows (exterior doors/roof windows only)
- \*\*\* Only applies to windows with integrated ventilation devices
- \*\*\*\* Certification in accordance with country of destination

Weißenfels, 28/1/2019  
p.p.

M. Herbst  
Spokesman for the Executive Management Board

p.p.

C. Fischer  
Head of Technology